




199.00 EUR
incl. 19% VAT, plus [shipping](#)

Support:  [Specifications \[EN\]](#)

- Intel® QM57 Express Chipset
- **Supports Intel Core™ i3, i5, i7 Mobile Processors**
- Dual Channel DDR3-800/1066 up to 8GB
- **Intel 82577LM Gigabit LAN**
- Intel Active Management Technology (iAMT 6.0)
- PCI Express x16 2.0 Slot, PCI Express Mini Card Slot
- **Integrated 24-bit Dual Channel LVDS**
- **5-port SATA 3Gb/s with RAID 0, 1, 5, 10 & JBOD Support**
- HDMI, DVI-D, and VGA Video Outputs
- Built-in Watchdog Timer Technology
- Mini-ITX Form Factor (170mm x 170mm)
- **Includes CPU Heatsink/Fan for <35W Processors**
- **CPU**
 - Intel Core i3, i5, i7 mobile processors
 - Socket G (rPGA988A), Includes CPU Heatsink/fan for <35W processors
- **Chipset / Video**
 - Intel QM57 Express Chipset
 - Intel HD Graphics (requires compatible CPU with built-in GPU)
- **Memory**
 - 2 * SODIMMs Sockets for un-buffered dual channel DDR3-800/1066 up to 8 GB
- **Expansion Slots**
 - 1 * PCI Express x16 2.0 (by 16-lane) slot
 - 1 * PCI Express Mini Card slot

- **Storage**
 - **Audio**
 - **Networking**
 - **LVDS**
 - **USB**
 - **Special Features**
 - **Rear I / O**
 - **Internal I / O**
 - **BIOS**
 - **Form Factor**
 - **Functional**
 - **Compliance**
 - **Temperature**
- 5 * Serial ATA II 3Gb/s connectors
 - VIA VT 1705 6-Channel HD Audio
 - Intel 82577LM Gigabit Ethernet LAN
 - Intel Active Management Technology support (iAMT 6.0)
 - Onboard 24-bit dual channel LVDS connector
 - Embedded 10 * USB 2.0/1.1
 - Supports ACPI S3, CPU Smart FAN, All solid capacitors
 - Watchdog hardware monitor
 - 6 * USB 2.0/1.1 ports
 - 1 * PS/2 KB/mouse combo connector
 - 1 * RJ-45 port
 - 1 * HDMI port
 - 1 * VGA port
 - 1 * DVI-D port
 - 1 * eSATA port
 - 1 * Audio port (Line-in, MIC and Line-out)
 - 1 * Coaxial Out & 1 * Optical Out
 - 2 * USB 2.0/1.1 headers for 4 USB ports
 - 1 * 24-bit dual channel LVDS header
 - 1 * Serial header (RS232/422/485)
 - 1 * GPIO header
 - 1 * Audio header, 1 * Front panel header
 - 1 * 24-pin ATX power connector, 1 * 4-pin 12V ATX power connector
 - AMI EFI 64MB SMT Flash ROM
 - Mini-ITX Form Factor (170mm x 170mm)
 - ATM, Automation, medical Equipment, Security, Networking, POS, General Application, Gaming Machine, Transportation
 - CE, FCC, RoHS, EuP
 - Operating within 0~60 centigrade
 - Storage within -20-85 centigrade

Product Accessories

- COM cable
- Manual
- CD
- 1x SATA cable
- I/O shield
- CPU fan
- Thermal grease