



249.00 EUR
 incl. 19% VAT, plus [shipping](#)

- NVIDIA 610M GPU !
- 5x SATA !



- INTEL® Cedar Trail-D Processor D2550 + ICH10R Chipset + NVIDIA® 610M GPU
- Support 2 * DDR3 1066MHz Single CH up to 8GB
- Support DirectX 11 Graphics up to 850MHz
- 5 ports Serial ATAII (3Gb/s) with RAID 0, 1, 5,10 supported
- Realtek ALC887 8-CH HD Audio CODEC
- Support HDMI, DP & DVI-I (Dual Link) Display output
- Supports 1 * Realtek RT8111F Gigabit LAN
- Support Watch dog Technology
- Support CPU Smart FAN
- Compliance with ErP standard
- Mini-ITX Form Factor (170mm x 170mm)

| | |
|------------------------|---|
| CPU | • INTEL® Cedar Trail-D Processor D2550 CPU (1.86GHz) |
| Chipset | • INTEL® ICH10R Express chipset |
| GPU | • Nvidia 610M |
| Memory | • 2 * DDR3 1066/800MHz Single CH SO-DIMM up to 8GB |
| Expansion Slots | • 1 * MINI PCI-E |
| Storage | • 5 * Serial ATAII 3Gb/s with RAID 0,1, 5, 10 supported • 1 * mSATA (Selectable with Mini PCI-E) |
| Audio | • Realtek ALC887 8-CH HD Audio CODEC |

| | |
|---------------------------|---|
| • Ethernet LAN | • 1 * RTL8111F PCI-E Gigabit LAN |
| • USB | • Embedded 8 * USB 2.0/1.1 |
| • Special Features | • Support ACPI S3 • Support CPU Smart FAN • Support Watch Dog |
| • Rear Panel I/O | • 4 * USB 2.0/1.1 ports • 1 * RJ-45 port • 2 * COM ports • 1 * DP port • 1 * HDMI port • 1 * DVI-I (Dual Link) port • 1 * Audio I/O port • 1 * +12V DC-in jack |
| • Internal I/O | • 2 * USB 2.0/1.1 headers for 4 USB 2.0 ports • CPU /NB / Chassis Fan connectors; • 1 * GPIO header • 1 * TPM header • 1 * CIR • 1 * Chassis Intrusion header |
| • BIOS | • AMI 16MB UEFI DIP Flash ROM |
| • Form Factor | • Mini ITX Form Factor(170mm x 170mm) |
| • Functional | • POS, Digital Signage, Gaming Machine, Kiosk |
| • Certificate | • CE, FCC, RoHS |
| • Temperature | • Operating within 0~60 centigrade • Storage within -20-85 centigrade |