

339.00 EUR

incl. 19% VAT, plus [shipping](#)

- Intel Elkhart Lake SoC !
- 2x LAN !



- Intel Elkhart Lake SoC Processor
- 1\* DDR4 3200MHz SO-DIMM up to 32GB
- 1\* HDMI, 2\* USB3.1, 1\* USB-C, 2\* RJ45, 1\* COM
- Support 9~36V wide voltage input
- DC12V\_40W Adapter

|                    |   |  |
|--------------------|---|--|
| Model              | – HBFBP01-6210-B<br>– HBFBP011-6210-B (WiFi model)  |  |
| CPU/Chipset        | – Intel® Elkhart Lake SoC Processor   |  |
| BIOS               | – AMI Flash ROM   |  |
| Memory             | – 1* DDR4 3200MHz Dual Channel SO-DIMM up to 32GB   |  |
| Storage            | – 1* M.2 M-key (2242, PCIe Gen.3 x2/SATA interface) support NVMe                                |  |
| Expansion          | – 1* M.2 E-key (2230, PCIe Gen.3 x1/USB2.0 interface)   |  |
| Rear Panel I/O     | – 2* RJ45<br>– 1* DC-in<br>– 1* HDMI<br>– 2* USB3.1(Gen.2) A Type<br>– 1* USB3.1(Gen.2) C Type  |  |
| Front Panel I/O    | – 1* Power button + Power LED<br>– 1* RS232/422/485   |  |
| Internal Connector | – 1* GPIO<br>– 2* USB2.0  |  |
| Power Source       | – Adapter : AC 90~240V input / DC12V_40W output / Lock type<br>– System : DC9~36V input support |  |
| Compliance         | – CE, FCC, LVD, RoHS, ErP Ready   |  |
| Dimensions         | – System: 125 (W) x 109 (D) x 44.5 (H) mm<br>– Color Box : 158 (W) x 167 (D) x 123.6 (H) mm     |  |

---

|             |  |
|-------------|--|
| Temperature | <ul style="list-style-type: none"><li>- Operating Temperature: -20 ~ 60° C (Under the condition of using M.2 interface SSD)</li><li>- Storage Temperature: -40 ~ 85° C</li><li>- Humidity: 10% ~ 95% RH @40°C (non-condensing)</li></ul> |
| OS Support  | <ul style="list-style-type: none"><li>- Windows 11, Linux</li></ul>  |