



99.00 EUR  
incl. 19% VAT, plus [shipping](#)



**Support:**  [Manual \[EN\]](#)

- Up to two 2.5" drives
- Bootable (IDE) Compact-Flash
- PWR button and LED
- Works with any picoPSU (not included)
- Size 20cm (w) x 5.4cm x 24cm

The M200-Enclosure is a versatile mini-ITX enclosure designed for embedded applications where CDROM drives are not required. The M200-Enclosure fits any type of mini-ITX board with standard back I/O shield. Not recommended for EPIA 800, EPIA 5000 and EPIA CN series because of the different USB header pinout. The M200-Enclosure will work with up to two IDE or SATA 2.5" disk drives (disk drive cable adapter not included).

The M200-Enclosure is compatible with an entire range of DC-DC picoPSU power supplies, allowing system designers to pick the right PSU for their application (picOPSU not included in this assembly)

The M200-Enclosure has a front door for extra ESB ports and Bootable Compact Flash adapter (included in this assembly), making this enclosure perfect for systems that boot from flash (Compact Flash).

The M200-Enclosure comes in a white OEM box that can be re-branded. The enclosure has a small area for OEM logo, allowing system integrator to re-brand the unit, making this enclosure the perfect candidate for embedded applications.