

CTF700-SP - VGA 7" TFT - Touchscreen USB - PAL/NTSC - IR Remote - Audio (500 nits) [LED-Backlight] (XENARC PIN-compatible)

[http://www.cartft.com/catalog/il/926]



289.00 EUR

incl. 19% VAT, plus shipping

- · High brightness!
- · Audio speakers!
- · Rear CAM feature!
- Auto-PowerOn!



Support: 800x480 Driver (Windows 7)

Model for Xenarc-Changers: CTF700-SP can be immediately used in place of a 700Y, 700TS, 700TSV, 800TSV,... The All-In-One cable is pin-compatible.

New : LED-Backlight-Technology, with optimized color saturation enabling particular high and shining display. The scale of displayable color nuances is increased by 45% because of the new technology. Conventional LCDs are based on CCFL backlight, which can display approx. 72% of the standard color scale of NTSC (National Television Systems Committee). With LED-Backlight-Technology 104% of the NTSC-color scale can be displayed. This results in displaying in a highly realistic manner.

The new CTF-700 TFT-Display is the ideal display- and input-unit for your Laptop, CarPC or HTPC. With the touchscreen functionality you easily can control your PC. The briliant VGA-display ensures a maximum readability and sharpness.

The device has integrated Stereo-speakers, a rear camera input and the dimmer button in the front will enable perfect viewing pleasure also during the night.

AC-Adapter for home usage and a car cigarette lighter adapter is included as well as the IR-remote-control unit and the extra long (2,5 meters) All-In-One connector cable.

The CTF-700 can be used with any PC/MAC with VGA- and USB port.

Driver-CD included, compatible with:



CTF700-SP - VGA 7" TFT - Touchscreen USB - PAL/NTSC - IR Remote - Audio (500 nits) [LED-Backlight] (XENARC PIN-compatible)

[http://www.cartft.com/catalog/il/926]

- Windows 95/98/ME/NT4/2000/XP/7/8/8.1/10
- XP Tablet PC Edition
- Windows CE 2.12, 3.0, .net
- Linux RedHat, Mandrake,...
- Macintosh OS 9.x, 10.x
- DOS,..

7" digital
16:9 wide TFT screen
2400x480= 1,152,000 dots
800x480
640x480-1024x768
RGB stripe
DC 12/24V
max. 8W
3x Video inputs (PAL/NTSC) (2x with CTF700-SP) 1x VGA input
Display Case : 184x129x32 mm Display : 154 x 93 mm
1.0Vp-p, composite video
400 cd/m ²
350:1
EC68-2-6
0° bis 70°C
Full function OSD control (englisch)
Built-in Stereo-speakers
Auto Power On/Off
Earphone-Output (rear side)
Automatic switching to rear camera (by signal detection on AV3) [not with CTF700-SP]
7" VGA Touchscreen TFT with Video/Audio-support
Infrared Remote Control
Car dash mounting bracket
- Touchscreen pencil
VGA/Video/Audio/Touchscreen-cable (all-in-one!) 2,5 meters length
Power Adapter f. EU 230V
Cigarette Lighter Adapter
- Touchscreen Driver-CD
- Manual



Displays with <u>True-800x480-Support</u> achieve a pixel accurate view at 800x480@70Hz